



PRESS-IN THREADED STUD


BFH, BFHS, BFHA, BFH4



Montage



BFH4
Montage



Thread d ₁	hole-Ø in metal sheet +0,08 0	d ₂ 0/-0,4	d ₃	Wrench- size sw	min thick- ness metal sheet sm	Dis- tance to mid- dle hole	Ordering description			Dis- tance to mid- dle hole	Ordering de- scription Stainless steel, passivated
							Steel, galvanized colorless passivated	Stain- less steel, passiv- ated	Aluminium		
M2,5	2,50	4,10	2,6	1,95	1,0	5,4	BFH-M2,5-L	BFHS-M2,5-L	BFHA-M2,5-L		
M3	3,00	4,6	3,1	2,10	1,0	5,6	BFH-M3-L	BFHS-M3-L	BFHA-M3-L	5,6	BFH4-M3-L
M4	4,00	5,9	4,1	2,40	1,0	7,2	BFH-M4-L	BFHS-M4-L	BFHA-M4-L	7,2	BFH4-M4-L
M5	5,00	6,5	5,1	2,70	1,0	7,2	BFH-M5-L	BFHS-M5-L	BFHA-M5-L	7,2	BFH4-M5-L
M6	6,00	8,2	6,1	3,00	1,6	7,9	BFH-M6-L	BFHS-M6-L	BFHA-M6-L	7,9	BFH4-M6-L
M8	8,00	9,6	8,1	3,70	2,4	9,6	BFH-M8-L	BFHS-M8-L	BFHA-M8-L		

Errors and changes excepted, length tolerance (L +/-0,4)

Type BFH:
carbon steel strength
class 8.8, core harde-
ned, galvanized, color-
less passivated (code
ZI), for sheet hardness
up to HRB-80

Type BFHS:
stainless steel 18/8
(AISI300), passivated,
for sheet hardness up
to HRB-70

Type BFHA: Aluminium,
for sheet hardness up
to HRB-50

Typ BFH4: stainless
steel 18/8 (AISI300),
passivated, for sheet
hardness up to HRB-92

			Length												
BFH-M2,5-L	BFHS-M2,5-L	BFHA-M2,5-L	6	8	10	12	15	18	-	-	-	-	-	-	-
BFH-M3-L	BFHS-M3-L	BFHA-M3-L	6	8	10	12	15	18	20	22	25	28	30	-	-
BFH-M4-L	BFHS-M4-L	BFHA-M4-L	6	8	10	12	15	18	20	22	25	28	30	35	38
BFH-M5-L	BFHS-M5-L	BFHA-M5-L	-	8	10	12	15	18	20	22	25	28	30	35	38
BFH-M6-L	BFHS-M6-L	BFHA-M6-L	-	-	10	12	15	18	20	22	25	28	30	35	38
BFH-M8-L	BFHS-M8-L	BFHA-M8-L	-	-	-	12	15	18	20	22	25	28	30	35	38

	Length									
BFH4-M3-L	6	8	10	12	16	18	20	25	-	-
BFH4-M4-L	6	8	10	12	16	18	20	25	30	35
BFH4-M5-L	-	8	10	12	16	18	20	25	30	35
BFH4-M6-L	-	-	-	12	16	18	20	25	30	35

Errors and changes excepted