



STANDARD NUT - FOR SHEET METAL

BS, BCLS



Montage



Type BS: carbon steel, strength class 10, galvanized, colorless passivated (code ZI), for sheet hardness up to HRB-80

Type BCLS: Stainless steel 18/8 (AISI302/303), for sheet hardness up to HRB-70.

Errors and changes excepted

Thread d_1	\varnothing in metal sheet +0,08 0	Maximum d_2	d_3 $\pm 0,25$	m $\pm 0,25$	h max	sm min	Distance to middle hole	Ordering description Carbon Steel, galvanized colorless passivated	Ordering description Stainless steel, passivated
M2	4,25	4,22	6,30	1,50	0,77 0,97 1,38	0,8 1,0 1,4	4,8	BS-M2-0 BS-M2-1 BS-M2-2	BCLS-M2-0 BCLS-M2-1 BCLS-M2-2
M2,5	4,25	4,22	6,30	1,50	0,77 0,97 1,38	0,8 1,0 1,4	4,8	BS-M2,5-0 BS-M2,5-1 BS-M2,5-2	BCLS-M2,5-0 BCLS-M2,5-1 BCLS-M2,5-2
M3	4,25	4,22	6,30	1,50	0,77 0,97 1,38	0,8 1,0 1,4	4,8	BS-M3-0 BS-M3-1 BS-M3-2	BCLS-M3-0 BCLS-M3-1 BCLS-M3-2
M4	5,40	5,38	7,90	2,00	0,77 0,97 1,38	0,8 1,0 1,4	6,9	BS-M4-0 BS-M4-1 BS-M4-2	BCLS-M4-0 BCLS-M4-1 BCLS-M4-2
M5	6,40	6,38	8,70	2,00	0,77 0,97 1,38	0,8 1,0 1,4	7,1	BS-M5-0 BS-M5-1 BS-M5-2	BCLS-M5-0 BCLS-M5-1 BCLS-M5-2
M6	8,75	8,72	11,05	4,08	1,15 1,38 2,21	1,2 1,4 2,3	8,6	BS-M6-0 BS-M6-1 BS-M6-2	BCLS-M6-1 BCLS-M6-2
M8	10,50	10,47	12,65	5,47	1,38 2,21	1,4 2,3	9,7	BS-M8-1 BS-M8-2	BCLS-M8-1 BCLS-M8-2
M10	12,70	12,67	16,50	7,90	1,48	1,5	12,0	BH-M10	-